



# TECHNICAL DATA BULLETIN

2059  
MONOLEX®  
Penetrating Oil  
And Lubricant

## DESCRIPTION:

An outstanding light, penetrating oil and lubricant. Works quickly to dissolve most rust, gum and varnish to free up frozen parts. Leaves a tough film of lubricant, plus rust and corrosion inhibitor. Displaces moisture. Contains MONOLEC®, LE's exclusive wear-reducing additive, plus a carefully designed package for penetration and protection.

## PHYSICAL CHARACTERISTICS - TYPICAL:

Viscosity:	
SUS @ 100°F	31.9
cSt @ 40°C	1.81
Gravity, °API	43.2
Flash Point, °F (°C)	160 (72)
Pour Point, °F (°C)	-38 (-39)
Color	Amber

## SPECIFICATIONS EXCEEDED:

USDA H2

## APPLICATION:

Penetrating oil, light chain lubricant and other similar applications. Mild parts cleaner. LE's 2059 is also available in aerosol cans which contain no chlorofluorocarbons.

## RECOMMENDATION:

Do not use to clean belts. Residual lubricant will cause slippage.

LEADERS IN LUBRICANTS

**LUBRICATION ENGINEERS, Inc.**

## **BENEFICIAL QUALITIES:**

Excellent penetrating oil, quickly loosening frozen components.

Dissolves most rust and washes away gum, resins, varnish and dirt.

Leaves MONOLEC<sup>®</sup> to reduce later bonding of metal parts.

Displaces moisture.

Excellent light lubricant for chains, conveyors and similar applications.

Will clean up mechanical parts (mild) and leave lubrication.