



# TECHNICAL DATA BULLETIN

## 8940 MONOLEC<sup>®</sup> Natural Gas Engine Oil

### DESCRIPTION:

Premium quality detergent engine oil for use in natural gas burning engines requiring low ash engine oil. Provides anti-wear protection, and oxidation and corrosion inhibitors. Contains MONOLEC<sup>®</sup>, LE's exclusive wear-reducing additive.

### PHYSICAL CHARACTERISTICS—TYPICAL:

SAE Grade	40
Gravity, °API	28.7
Viscosity,	
SUS @ 100°F	735.0
SUS @ 210°F	74.82
cSt @ 40°C	140.5
cSt @ 100°C	13.92
HTHS Viscosity @ 150°C, cP, ASTM D-4683	3.7 min.
Viscosity Index	95
Color	Red
Flash Point °F (°C)	465 (240)
Pour Point °F (°C)	0 (-18)
Total Base Number (TBN), ASTM D-2896	5.1
Sulfated Ash, Mass%, ASTM D-874	.35 - .50

### SPECIFICATIONS EXCEEDED:

API CF	Waukesha Co-Gen	Cooper-Bessemer
Superior	Wartsila	Jenbacher
Dresser-Rand Category III	Ingersoll Rand	Caterpillar

LEADERS IN LUBRICANTS

**LUBRICATION ENGINEERS, Inc.**

## **APPLICATION:**

Meets the requirements for most large stationary engines, standby generators and co-generation engines using natural gas as fuel.

## **BENEFICIAL QUALITIES:**

Superior oxidation inhibitor.

Excellent detergent action.

Contains MONOLEC®.

Excellent wear protection.

LI50047  
07-99  
SS081898  
TDBS18940